

# CITIZEN

## High speed, LCD control POS printing

Retail class leader



### LCD display

The industry's first POS printer with LCD display for easy configuration and operation. Many set up options and coloured status or error messages.

### In a hurry?

With 300mm/sec. print speed the CT-S801II is the fastest POS printer in the market.

### Tool-free maintenance

Paper jam? No problem for the CT-S801II. One hand grip and the cutter is released automatically. No tool is needed. Even if the long-life cutter ever needs to be exchanged. Thanks to it's snap-In design this only takes 30 seconds.

## CT-S801II

POS, Receipt printer (thermal 3 inch / 80mm)

### Applications

- Hospitality
- Kiosk
- Kitchen
- Retail



Fast, easy and reliable

TOMORROW'S PRINTING TODAY



Full range of interface options incl. Bluetooth® (Apple™ and Android™ compatible).

## Specifications

## CT-S801II

**POS, Receipt printer (thermal 3 inch / 80mm)**

### Features & Benefits

- Paper exit: Top exit - ideal for all retail applications
- Paper load: Easy paper loading
- Printing Speed: Ultra fast print out of receipts - up to 300mm per seconds
- Display: LCD display for easy configuration and operation
- Low space requirement - integrated power supply enables clean work station
- Mobile-POS ready
- Easy notification - built-in buzzer
- ENERGY STAR® compliant
- Small footprint
- Recyclable packacking



High speed printing with unique ease of use

# CITIZEN

## CT-S801II

POS, Receipt printer (thermal 3 inch / 80mm)

<b>Model</b>	<b>CT-S801II</b>
<b>Printing Technology</b>	Direct Thermal
<b>Resolution</b>	203 dpi
<b>Print Speed (maximum)</b>	300 mm/sec.
<b>Print Width (maximum)</b>	45 / 48 / 52 / 54 / 64 / 68 / 72 / 80 mm
<b>Media Width (min to max)</b>	58 / 60 / 80 / 82.5 mm
<b>Media Thickness (min to max)</b>	65 to 75 µm or 75 to 85 µm
<b>Main Interface</b>	None: interface card slot for optional card
<b>Interface</b>	Ethernet + USB host, Premium Wireless LAN, Bluetooth with Apple™ MFi compatibility, Compact Wireless LAN, Serial (RS-232C compliant), Parallel (IEEE 1284 compliant), USB, USB with hub, Powered USB
<b>Power supply</b>	110 - 240 V, 50/60 Hz
<b>Reliability</b>	200 Million pulses or 150 Km, 2 million cuts
<b>Emulations (Languages)</b>	ESC/POS™
<b>Drivers and software</b>	Free-of-charge from website, including support for various platforms
<b>Size (W x D x H) and Weight</b>	145x192x148 mm, 2 Kg, DC version 145x192x120, 1.6 Kg
<b>Cutter</b>	Guillotine type, full and partial
<b>Warranty</b>	2 years including head and cutter
<b>EMC and safety standards</b>	CE, TUV, UL, C-UL, FCC class A, VCCI

# CITIZEN

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

## CT-S801II

**POS, Receipt printer (thermal 3 inch / 80mm)**