

Affordable Premium Performance



## PB-4700

### Advanced POS BOX

The PB-4700 is an advanced compact POS box, ideally suited for most retail sectors and cash till areas, where the space is at a premium. It brings greater value to the store owner through compact design, robust performance and superior consumer experience.

# PB-4700

## Compact and Flexible

The small footprint of PB-4700 allows for easy installation in anywhere you need a Point of Service system.

## Scalable Performance

The PB-4700 comes with multiple Intel CPU selection that ranges from Celeron all the way to Core i7, which delivers scalable performance to fit each unique need.

## Expandable and Configurable

Connect to a wide range of POS peripherals and options for greater productivity and flexibility to fit in your store environment.

Specification	PB-4700
Processor	Intel Haswell G1820 CPU, 2.70 GHz, 2M Cache; Intel Haswell G3320TE CPU, 2.30 GHz, 3M Cache; Intel Haswell Core i3-4330TE CPU, 2.40 GHz, 4M Cache; Intel Haswell Core i5-4570TE CPU, up to 3.30 GHz, 4M Cache; Intel Haswell Core i7-4770TE CPU, up to 3.30 GHz, 8M Cache
System Memory	DDR3L SO-DIMM x 2, max. 16GB
Storage Device	SATA Storage x 2
Power Supply	12V/80W
OS Support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux per request

## I/O & Expansion

Serial Port	4, DB9 x 4, optional COM5/COM6 via daughterboard, 5V/12V support on all COM ports
Parallel Port	Yes
Standard USB Port	USB 2.0 x 6 + USB 3.0 x 2
PoweredUSB Port	Optional 24V + 12V x 1 via daughterboard
LAN Port	10/100/1000 Mb x 1
Display Port	VGA x 1, DP x 1, 12V support on main VGA port for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
PS/2 Port	Yes
Audio	Line-out/Mic-in, optional internal speaker x 1
Expansion Slot	PCI-E slot x 1, via Riser card

## Physical Dimension

Dimension (W x D x H in mm)	279 x 243 x 114
Weight (N. W. in kg)	2.5

## Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

\*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

\*The product information and specifications are subject to change without prior notice.

Certifications	      	EN201710V2
----------------	--	------------

**POSIFLEX**

### POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan  
Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw  
Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller