

Palm-sized printers, perfect for printing on the move

RJ-2035B / RJ-2055WB
RJ-3035B / RJ-3055WB



PRINT



WIRELESS



BLUETOOTH

brother.co.uk/mobile-printers/ruggedjet

Name: P. Schmidt
CSC Security
Issue: 03.02.201
Expire: 03.02.201
0770

BROTHER CITY
PARKING VIOLATIONS
COURT OF JUSTICE



DATE: 01/01/2020
TIME: 14:37
NUMBER PLATE: SB16 CBR
VEHICLE MAKE: BMW
LOCATION: Centre car park

COMMENTS: Car was parked 30 minutes past parking ticket expiry time.

FINE: €40.00

Violation notice was served to the owner of the vehicle identified herein by affixing to the vehicle.

Our lightest mobile printers yet

These RJ mobile printers are ideal for printing receipts, tickets and labels.

Lightweight and compact, the 2" and 3" receipt printers have a range of connectivity options and integrate easily into your existing systems thanks to the supported printer command languages and free of charge Software Development Kits.

Key features:

- Portable compact design: 2.5m drop tested and IP54 rating with optional case
- Ready to integrate with iOS® and Android apps
- Compatible with Windows®
- Easy to use with USB, Bluetooth and wireless connectivity options
- Fast print speeds up to 4ips (101mm/sec)
- Battery indicator for LED charge status.

Compact and ultralight design

Linerless media support (dealer option)

Wireless LAN supporting 2,4GHz and 5GHz bands^



Bluetooth interface

NFC for easy pairing

Extended printer command language support



General

Carton contents

Belt clip
Power adaptor
Battery
Documentation

Language support

Danish, Dutch, English, Spanish,
French, Italian, Norwegian,
Portuguese, Finnish, Swedish

Dimensions and weights

RJ-2035B/RJ-2055WB:

79(w) x 36.5(h) x 116(d)

RJ-3035B/RJ-3055WB:

105(w) x 49.5(h) x 116(d)

Without carton
(with battery)

215g

375g

Built-in features

Printing method

Direct thermal

Print speed

Maximum 4ips

Maximum print width

48mm: RJ-2035B/RJ-2055WB

72mm: RJ-3035B/RJ-3055WB

Maximum print length

2794mm

Print resolution

203dpi

Number of labels per battery charge

RJ-2035B

Approx. 36m or 510 labels

RJ-2055WB

Approx. 20m or 279 labels

RJ-3035B

Approx. 90m or 1260 labels

RJ-3055WB

Approx. 54m or 750 labels

(*Under Brother standard environment)

Interfaces

USB Ver.2.0 (Full Speed) (Micro)

Bluetooth version.4.2

RJ-2055WB/RJ-3055WB

Bluetooth version.5.0 MFi

RJ-2035B/RJ-3035B

Wireless LAN IEEE802.11a/b/g/n

supporting 2.4GHz and 5GHz

RJ-2055WB/RJ-3055WB

NFC (Passive)

Bluetooth profile

RJ-2035B/RJ-3035B:

Classic; Serial port profile (SPP),
GATT (low energy)/ iAP supported

RJ-2055WB/RJ-3055WB:

Classic; Serial port profile (SPP)

WLAN Security

RJ-2055WB/RJ-3055WB:

Authentic method (encryption scheme)

Infrastructure mode:

- Open system (None/WEP64/
- WPA/WPA2 PSK (TKIP+AES)
- EAP FAST (TKIP/AES)
- PEAPv0 (TKIP/AES)
- EAP TLS (TKIP/AES)
- EAP TTLS (TKIP/AES)

Printer commands

FBPL-EZC (EPL2/ZPL2/CPCL)

FBPL-EZP (EPL2/ZPL2/ESC POS) download

Printer driver

Microsoft® Windows® 7 / Windows® 8.1 / Windows® 10
Microsoft® Windows® Server 2012 / Server 2012R2 / Server 2016 / Server 2019
MAC OS: v 10.11 - 10.15

Linux: Ubuntu V11.04 16.04, Fedora 24
SUSE Linux Enterprise Server 12,
CentOS Linux 7.2
Red Hat Enterprise 7.3

Windows SDK

Microsoft® Windows® 7 / Windows® 8.1 / Windows® 10

Microsoft® Windows® Server 2012 / Server 2012R2 / Server 2016 / Server 2019

Mobile SDK

Android v5-v10
iOS v9-v13.2

Requires 3rd party app development using Brother SDK. Further information available at www.brother.eu/developer

Software

BarTender Ultra Lite Edition
Barcode label design software

Brother Printer Management Tool
Software to centrally manage devices for updating settings, firmware and other configurations. (Microsoft® Windows® 7 / Windows® 8.1 / Windows® 10 only).
Microsoft® Windows® Server 2012 / Server 2016 / Server 2019)

Internal fonts and sizes

8 Alpha-numeric bitmap fonts for FBPL2
Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
Downloadable font support via BPM software

Barcode symbology

Linear:
Code128UCC, Code128 subsets A, B, C, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Standard 2 of 5, Industrial 2 of 5, Code39, Code39 with check digit, Code93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, EAN14, Code11, TELEPEN, TELEPEN number, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS.

2-Dimensional:
CODABLOCK F mode, GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF417.

Environmental

Drop protection
1.8m (without IP54 case)
2.5m (with IP54 case option)
(Under Brother standard environment)

Sealing
IP42 without case
IP54 with case (option)

Operating temperature
-15°C to 50°C

Operating humidity
10% to 90% non-condensing

Charging temperature
0°C to 40°C

Storage temperature
-30°C to 70° C

Supplies

Media

BDE-1J000057-030

Direct thermal receipt roll
RJ-2035B | RJ-2055WB | RJ-3055WB
Label size 57mm x 6.6m
Colour: white

BDE-1J000079-040

Direct thermal receipt roll
RJ-3035B | RJ-3055WB
Label size: 79mm x 14m
Colour: white

BDE-1J044076-040

Direct thermal die-cut label rolls
RJ-3055WB
Label size: 76 x 44mm
quantity: 70 labels per roll
Colour: white

Optional accessories

Cases

RJ-2035B/RJ-2055WB:

PA-CC-002 IP54
Protective case with shoulder strap

RJ-3035B/RJ-3055WB:

PA-CC-003 IP54
Protective case with shoulder strap

All models:

PA-SS-001 Shoulder strap with adapter

Power options

RJ-2035B/RJ-2055WB:

PA-4BC 001 4-bay battery charger
PA-CR 003 Single-bay cradle/charger**
PA-4CR 001 4-bay cradle/charger**

RJ-3035B/RJ 3055WB:

PA-BC 005 Single-bay battery charger
PA-4BC 002 4-bay battery charger
PA-CR 004 Single-bay cradle/charger**
PA-4CR 002 4-bay cradle/charger**

All models:

PA-CD 001CG Cigarette lighter plug**

Battery

RJ-2035B/RJ-2055WB:

PA-BT 008 Rechargeable Li-ion battery

RJ-3035B/RJ 3055WB:

PA-BT 009 Rechargeable Li ion battery
PA-BT 010 Rechargeable Li ion Smart battery

Media handling

RJ-2035B/RJ-2055WB:

PA-LPR 002 Linerless kit^^
PA-RS 001 Roll spacer

RJ-3035B/RJ-3055WB:

PA-LPR 003 Linerless kit^^
PA-RH 002 Roll holder
PA-RS 002 Roll spacer

*Connected by Wi-Fi or Bluetooth communications with new battery and full charge. Printed by Brother specified data (12.5% coverage 72mm media length)

**Accessory coming soon. ^RJ-2055WB and RJ-3055WB only. ^^ Dealer option only.



Working with you for a better environment

At Brother, our green initiative is simple. We strive to take responsibility, act respectfully and try to make a positive difference to help build a society where sustainable development can be achieved. We call this approach Brother Earth.

brotherearth.com

All specifications correct at the time of printing (June 2020) and are subject to change. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks or trademarks of their respective companies. CD3155.

brother
at your side