

XT-5515

POSIFLEX

Specification	XT-5515
Processor	Intel Haswell Core i5-4570TE CPU, up to 3.30 GHz, 4M Cache; Intel Haswell Core i7-4770TE CPU, up to 3.30 GHz, 8M Cache
System Memory	DDR3L SO-DIMM x 2, max. 16GB
Storage Device	SATA x 2, SATA HDD x 2
RAID Function	Yes
Intel vPro Support	Intel AMT Only
TPM Support	TPM1.2
Power Supply	12V/130W
OS Support	Win 7/POSReady 7/WE 8.1 Industry/Win 10 IoT/Linux per request
Display & Touch	
LCD	15" TFT LCD
Resolution	1024 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)
I/O & Expansion	
Serial Port	6, DB9 x 2 + RJ45 x 2, pin header x 2 from service window, 5V support on all COM ports, 12V support on COM 1 to COM 4
Parallel Port	1, via optional conversion cable through service window
Standard USB Port	6, USB 3.0 x 2 + USB 2.0 x 4
PoweredUSB Port	Optional 24V x 1 + 12V x 3 via GEN8E base
LAN Port	10/100/1000 Mb x 2
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
PS/2 Port	1, via optional conversion cable through service window
UPS Port	Yes
Audio	Internal 2W speaker x 1 + Line-Out/MIC-In Combo Jack
Expansion Slot	Mini-PCIe slot x 1
Physical Dimension	
Dimension (W x D x H in mm)	372 x 320 x 252.7
Weight (N. W. in kg)	5.86
Environmental	
Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH
Built-in Options	
WiFi	Mini-PCIe WiFi/BT module
Attachment Options	
POS Monitor	Non-touch TFT LCD: 7" (bezel type)/9.7" (bezel-free/bezel type)/12.1"/14" (bezel-free)/15" (bezel-free/bezel type); PCAP touch TFT LCD: 9.7"/14"/15"; Resistive touch TFT LCD: 15"
Line Display	2 x 20 rear-mount VFD/LCD customer line display; 7" color LCD graphical customer line display
Peripherals	MSR; iButton; Rotatable 2D scanner; RFID; Fingerprint Sensor; Key Keypad

* Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

* The product information and specifications are subject to change without prior notice.

* Please refer to the website for more attachment options.



POSIFLEX

POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan
Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw
Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller

Flexible! Powerful! Elegant!



XT-5515

High-End Fanless POS Terminal



In today's retail and hospitality markets, POS terminal is no longer just a cold and hard business tool. It is a part of the store decoration, a part of the store image. Each curve and detail of the POS terminal should add something to the overall mood of the store, to lift the shopping experience of customers.

The XT-5515 features a 15" true-flat PCAP touch screen, beautifully sculptured slim body, and sexily curved base stand, it looks right at home at any elegantly decorated store. More than just good looks, the XT-5515 offers ample of performance and flexibility to satisfy the most demanding daily POS operations.

Sleek Look

The XT-5515 comes from new Posiflex design language. Slimmer than ever, it is a sharp departure from the traditionally conservative Posiflex terminal design. Every curve and detail of the XT-5515 is carefully thought out to make itself one of the most visually desirable terminals in the market.

Powerful Performance

The XT-5515 offers high-end Intel Core i5 or Intel Core i7 processor that is powerful enough to process anything throws at it without even breaking a sweat.



Multi-Position Folding Base (U.S. Patent 9004436)

The XT-5515 provides the selection of two foldable bases, the curvy slim GEN7E base and the larger but practical GEN8E base. This patented foldable base enables users to adjust the screen to a height and angle of their choice, providing unparalleled flexibility.



Full Extended Mode



Low Profile Mode



Flat Folded Mode

Management & Security

The XT-5515 comes with management and security features in Intel AMT, TPM and RAID.

Patented Fanless Technology

Solve the fan maintenance issue and provide silent mode operation, which is ideally suited for high-end boutique stores or hospital environments.



Power Adaptor

UPS Battery

PoweredUSB Ports

GEN8E Base (U.S. Patent 9004436)

Optional GEN8E base integrates internal power adaptor and PoweredUSB port into the base stand, which keeps counters clutter-free.